



FLAMMABLE GAS DETECTOR

Omniguard® model 1100

The Omniguard® model 1100 gas detector is designed to detect and measure the presence and level of flammable gases in industrial applications such as refineries, drilling and production platforms, gas turbines, chemical plants, fuel loading facilities, compressor stations, waste water treatment facilities, LNG/LPG processing and storage facilities, transportation facilities and manufacturing processes.

The Omniguard® model 1100 gas detector is based on well proven sensor technology and has fast response time, excellent measuring accuracy and long term stability. The microprocessor controlled functionality and the simple calibration procedure makes the Omniguard® 1100 gas detector easy to use and maintain and very reliable in field operation. Easy to read display, standard 4-20 mA and HART rev 7 output makes installation and operation of the detector quick and easy.

Specifications


General specifications

Measuring type	Diffusion
Measuring method	Catalytic cell, Thermal conductivity cell, Semiconductor cell
Detectable gases	Flammable gases (LNG, LPG, H ₂ , Methane, Buthane etc)
Measuring range	Depending on gas
Accuracy	≤ ±3% / Full range
Zero drift	≤ ±2% / Full range
Response time	Typical 90% of range in less than 15 seconds
Basic interface	Analog 4-20 mA current interface
HART interface	HART rev 7
Certification	<p>II 2 G, Ex db IIC Gb T4, T5, T6</p> <p>Classified for use in hazardous locations</p> <p>Class I, Division 1, Groups A, B, C, D hazardous locations. UL Certificate of Compliance E506030</p> <p>SIL2 SGS TÜV Certificate number: FS/71/220/20/0568</p>
Protection class	IP66
Operating temperature	<p>Transmitter: -40°C to +80°C (-40°F to +176°F)</p> <p>Sensor: Depending on sensor</p>
Operation humidity	<p>Transmitter: 5 to 99% RH (non-condensing)</p> <p>Sensor: Depending on sensor</p>
Pressure range	90 to 110 kPa
Max air velocity	6 m/s

Key features

- Wide range of detectable gases
- HART rev 7 communication as standard
- Advanced self-test and diagnostics
- Smart programming and auto calibration
- 4-20 mA output signal
- Easy in field calibration and maintenance
- Robust weather- and flame proof enclosure for indoor or outdoor applications
- Low cost of ownership
- IECEx, ATEX, UL, SIL2, CE

Specifications continue on next page...




Omniguard® model 1100

Specifications (continued)

Electrical specifications

Input voltage	18 to 31 VDC Nominal: 24 VDC Ripple voltage: <1 V
Power consumption	Max. wattage: 4.8W@+24 VDC Max. current: 200 mA@+24 VDC
Current loop	0-20 mA (source or sink), 500 ohms max load
Measured value signal:	4 mA (zero) to 20 mA (full range)
Fault:	0 mA
HART Fault:	2 mA
Maintenance:	3 mA
0-100%:	4 mA-20 mA
100-109%:	20 mA-21.4 mA
Over 110%:	22 mA
Current loop ripple & noise max	±20 µA
Wiring requirement	Power CVVS or CVVSB with shield Analog CVVS or CVVSB with shield
Signal transmission distance	Analog: 2500 m (8200 ft)
EMC protection	Complies with EN50270
Mechanical considerations	
Housing	Aluminium (ALDC) or Stainless steel (316) Sensor: Stainless steel (316)
Weight	1.5 kg (3.3 lbs) (aluminum) 3.1 kg (6.8 lbs) (SS)
Dimensions	136 (W) x 166 (H) x 110 (D) mm (5.4 (W) x 6.5 (H) x 4.3 (D)) in
Conduit entry	3/4-14 NPT or M20-1.5
Mounting holes	Ø 7 ±0.1 (Ø 0.28 in)
Accessories/Spare Parts	
Rain cover, plastic	Art.no 27727
Rain cover, SS (304)	28368
Collecting cone	27729
Pole mount	28236
Splash guard	27728
Magnet bar	27730
Sensor module	1100-S

Warranty 2 years (Transmitter) / 1 year (Sensor)



Omniguard 1100DS - Ver 1.5 | EN
© Firefly AB (2024)

Ordering information

Type	Omniguard® model 1100
Designation	Flammable gas detector
Ordering number	1100 - X X X X X X X
Housing material/conduit entry	
0	Aluminium, 3/4-14 NPT (white)
1	Stainless steel, 3/4-14 NPT
2	Aluminium, M20-1.5 (white)
3	Stainless steel, M20-1.5
Detectable gas	
0	CH ₄ (Methane)
1	C ₄ H ₁₀ (Buthane)
2	C ₃ H ₈ (Propane)
3	H ₂ (Hydrogen)
9	Other, please specify
Measuring method	
0	Semiconductor cell
1	Thermal conductivity cell
2	Catalytic cell
Measuring range	
0	0-2000 ppm (C ₄ H ₁₀)
1	0-100% Vol (H ₂)
2	0-100% LEL (CH ₄ , C ₄ H ₁₀ , C ₃ H ₈ , H ₂)
9	Other, please specify
Output signal	
0	4-20 mA, and HART rev 7
Configuration	
0	Standard
1	Remote option
Approvals	
0	IECEX, ATEX, UL, SIL2, CE



For information on the specific certifications and approvals each Omniguard® Gas Detector holds please visit:
www.omniguardbyfirefly.com/our-certifications/

Firefly AB
Stockholm, Sweden
Phone: +46 (0)8 449 25 00
E-mail: omniguardsales@firefly.se
www.omniguardbyfirefly.se

